



Lokong Bearing Co., Ltd.



10 mm x 30 mm x 9 mm
 HH221430/HH221410D Double Row Tapered
 Roller Bearing 76.2x190.5x127mm

Bearing No. 6200

6200 Bearing 2D drawings and 3D CAD models

Size	10x30x9 mm
Bore Diameter	10 mm
Outer Diameter	30 mm
Width	9 mm
d	10 mm
D	30 mm
B	9 mm
C	9 mm
r min.	0,6 mm
da min.	14 mm
da max	16 mm
Da max.	26 mm
ra max.	0,6 mm
Weight	0,032 Kg
Basic dynamic load rating (C)	5,1 kN
Basic static load rating (C0)	2,39 kN
(Grease) Lubrication Speed	24 000 r/min
(Oil) Lubrication Speed	30 000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.01
EAN	0029176013546



Lokong Bearing Co., Ltd.

Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	10MM Bore; 30MM Outside Diameter; 9MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nskamericas.com
Manufacturer Item Number	6200
Weight / LBS	0.029
Outside Diameter	1.181 Inch 30 Millimeter
Outer Race Width	0.354 Inch 9 Millimeter
Bore	0.394 Inch 10 Millimeter
bore diameter:	10 mm
closure type:	Open
outside diameter:	30 mm
internal clearance:	Normal Clearance
overall width:	9 mm



Lokong Bearing Co., Ltd.

manufacturer upc number:	029176013546
bore type:	Round
SRI	2.46
hidYobi	6200
LangID	1
D_	30
SREX	0.03
B_	9
da min	14
hidTable	ecat_NSRDGB
Oil rpm	30000
SRE	2.52
mass	0.032
GRS rpm	24000
ra	0.6
SRIX	0.015
D_a	26
SRIN	-0.015
C0	2.39
fo	13.2
SREN	0
DE_	25.262
Prod_Type3	DGBB_SR_OT
DA_	4.762
bomp	0
Z_	8
yobi	6200
C_conv	5100
ALPHA_	0
SDM_	20.5
r	0.6
KBRG	6101



Lokong Bearing Co., Ltd.

SBRG	2
DI_	15.738